Armand M. Vozzo,/ Regis. No. 28,818





Sir:						•		
Transmitt	ed herewith fo	or filing is	the patent	applica	ation of		010	
Inventor: James J. Sheehy, Jr.								
For:	For: CLIP SYSTEM FOR HOLDING VISE PARALLELS							
Enclosed	are:						(%)	
xx Fou	⊈.(4) shee	ts of drawing	. (in dup	licate) [.]	•		S
An a	ssignment of	the invention	to					
	•	•						
☐ A ∞	ertified copy	of a				applicat	ion.	
An a	ssociate powe	r of attorney	<i>7</i> •		•			
	wrified statem 37 CFR 1.27.	ent to establ	Lish small	entity:	status u	nder 37 C	FR 1.9	
	oress Mail Co	artificate		• :				
fire the same of t				•		•		
The filir	ng fee has bee	n calculated	as shown b	elow:				
and from	(Col. 1)	(Col.2)		SMALL I	ENTITY		OTHER SMALL	
FOR:	NO. FILED	NO. EXTRA		RATE ·	FEE	OR	RATE	FEE
BASIC FEE					#380W	OR		
TOTAL CLAIMS	6 -20=	* -0-		=	\$	OR	==	\$
INDEP CLAIMS	2 -3=	× -0-	1	=	\$	OR	=	\$
MULTIPLE I	EPENDENT CLAI	M PRESENTED		=	\$	OR	=	\$
	ference in Co , enter "0" in		J	TOTAL	\$380.au	OR	TOTAL	ş
								`.
Plea S	ase charge my	Deposit Accou A duplicate o		s sheet	is encl	in the am	ount of	
x A c	neck in the am	-		•		•	enclose	ed.
	commissioner					-		
fees associated with this communication or credit any overpayment to Deposit Account No A duplicate copy of this sheet is								
	losed.		··································	· dapare	ucc copy	01 4.15	3,,,,,,	•
	Any a	dditional fil	ling fees 1	required	under 3	7 CFR 1.1	.6.	
		catent applica	_	=				
fee Dep	Commissioner s during the posit Account blosed.	cendency of the	his applica	ation or	credit	any overr	payment :	to
	Any patent application processing fees under 37 CFR 1.17.							
	The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).							
		filing fees w					extra	

350 South Main Street Suite 117 Doylestown, PA 18901

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re appli	cation of: James J. Sheehy, Jr.
Serial No.	Group No.:
Filed:	Examiner:
For: CL	IP SYSTEM FOR HOLDING VISE PARALLELS
	oner of Patents and Trademarks on, D.C. 20231
	EXPRESS MAIL CERTIFICATE
"Express N	Mail" label number <u>EK227483850 US</u>
	eposit
	ereby certify that the following attached paper or fee
	Original patent application with drawings;
	Declaration/Power of Attorney; and
	Independent Inventor and Small Entity Affidavit and associated fee.
Addressee'	eposited with the United States Postal Service "Express Mail Post Office to service under 37 CFR 1.10 on the date indicated above and is addressed to the oner of Patents and Trademarks, Washington, D.C. 20231.
	Armand M. Vozzo, Jr.
	(Typed or printed name of person mailing paper or fee)
	// (Signature of person mailing/paher or fee)

	Applicant or Patentee: <u>James J. Sheehy</u> , <u>Jr.</u>	Attorney's
	Serial or Patent No.:	Docket No.: P603
	Filed or Issued:	
	For: CLIP SYSTEM FOR HOLDING VISE PARALLELS	
	VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL (37 CFR 1.9(f) and 1.27(b)) - INDEPENDENT	
	As a below named inventor, I hereby declare that I dindependent inventor as defined in 37 CFR 1.9(c) for paying reduced fees under section 41(a) and (b) of States Code, to the Patent and Trademark Office with invention entitled CLIP SYSTEM FOR HOLDING VISE PARA described in	r purposes of Title 35, United I regard to the
	<pre>x the specification filed herewith application serial no. , fi patent no. , issued</pre>	.led
and then said wife if if	I have not assigned, granted, conveyed or licensed a obligation under contract or law to assign, grant, of any rights in the invention to any person who could as an independent inventor under 37 CFR 1.9(c) if the invention, or to any concern which would not quabusiness concern under 37 CFR 1.9(d) or a nonprofit 37 CFR 1.9(e).	and am under no convey or license, not be classified nat person had made alify as a small
	Each person, concern or organization to which I have granted, conveyed, or licensed or am under an obligation to law to assign, grant, convey, or license invention is listed below:	ation under
•	no such person, concern or organization persons, concerns or organizations listed be	oelow*
	*NOTE: Separate verified statements are require person, concern or organization having rights averring to their status as small entities. (to the invention
	FULL NAME	
	ADDRESS Individual Small Business Concern Nonprofit Organization	

FULL NAME							
ADDRESS		•					
	Individual						
Small Busine Nonprofit Or							
Nonprofit of	ganizacion						
FULL NAME							
ADDRESS							
Individual							
Small Busine Nonprofit Or							
Nonproffe of	ganizacion						
I acknowledge the duty t	o file, in this applications in status resulting in	on or patent,					
to small entity status p	rior to paying, or at the	time of paying, the					
earliest of the issue fe	e or any maintenance fee	due after the date on					
1.28(b)).	entity is no longer approp	priate. (37 CFR					
	-						
I hereby declare that al	l statements made herein	of my own knowledge					
	atements made on informat: further that these state						
the knowledge that willf	ul false statements and the	he like so made are					
punishable by fine or imp	prisonment, or both, under	r section 1001 of					
	tates Code, and that such e the validity of the app						
patent issuing thereon,	or any patent to which the						
is directed.							
James J. Sheehy, Jr.							
NAME OF INVENTOR NAME OF INVENTOR NAME OF INVENTOR							
JSY		•					
Signature	Signature	Signature					
of Inventor	of Inventor	of Inventor					
11-1-99							
Date	Date .	Date					
•							

10

25

20

CLIP SYSTEM FOR HOLDING VISE PARALLELS

BACKGROUND OF THE INVENTION

The present invention relates to the positioning of a workpiece in a vise for machining, and more particularly to an improved clip system for holding parallel plates against respective jaws of the vise in proper position to mount the workpiece during machining.

A vise is commonly used to secure a workpiece intended to be machined. Typically, the workpiece is mounted within the opposite jaws of the vise and secured in proper position therebetween using a pair of flat, metal plates known as parallels. These parallels, which may be of varying widths and thicknesses, are mounted immediately adjacent to the respective jaws in substantially identical positions on either side of the vise so that their upper margins act as reference surfaces for the mounting of the workpiece between the vise jaws. The parallels thus serve to mount the workpiece in an exact attitude while machining and it is essential that the parallels be held securely in place against the jaws in order for the workpiece to be machined correctly.

In the past, a number of different devices have been used to hold the parallels against the jaw surfaces. For instance, spring members have been inserted in the space between the parallels in pressing engagement with the parallels themselves with the springs being under compression. While these spring members have effectively served to position the parallels pressed against the vise jaws they can become easily dislodged under working conditions and hurdle through space, risking bodily injury to a workman adjacent to the workpiece. Other, more elaborate systems have been used

25

5 10 15 Con Car Se Se

1

but these have been expensive to produce and complex to use, and they require considerable amount of space for use in holding the parallels in place. Some of these more elaborate prior art holding systems have required substantial modifications to the standard jaws of a machine vise in order to implement their use and operation, and in many cases, the costs and effort to adapt those holding systems to existing vises has been burdensome. Furthermore, most of these existing systems have been devised and developed for disposition and operation within the spatial confines between the opposed vise jaws. As a result, these existing holding systems may sometimes interfere with the positioning of the workpiece between the jaws and disrupt its proper attitude for machining. A need therefore exists for an improved parallel holding system that works safely and effectively without interfering with the position of the workpiece while machining, and that can easily adapt to existing machine vises.

10

20

SUMMARY OF THE INVENTION

Accordingly, it is a general purpose and object of the present invention to provide an improved system for holding parallels properly in place against the jaws of a vise.

Another object of the present invention is to provide an improved parallel holding system that is safer and easier to use on existing machine vises without interfering with a workpiece while it is being machined.

Still another object of the present invention is to provide a parallel holding system that is easily adapted to existing vises and that is effective in holding parallels of various sizes in proper position against the vise jaws.

A still further object of the present invention is to provide a parallel holding system that is easy to manipulate and reasonably inexpensive to manufacture and implement.

Briefly, these and other objects of the present invention are accomplished by an improved clip system for holding parallels in place against the respective jaws of a vise. The clip system comprises a pair of specially configured clip members adapted to releasably engage a retaining plate mounted flush between the jaw and the vise, the retaining plate being formed having a slotted tab extended from either side of the plate for engaging a respective one of the clip members. Each clip member is integrally formed having a hook section inwardly disposed at an intermediate position along its length to engage the slotted tab in a forwardly direction and a cap section inwardly disposed at the forward end of the clip member to clamp flush against the parallel and hold it firmly against the jaw when the hook section is engaged with the slotted tab. The clip members are

25

20

further formed each having an outwardly disposed leg section intended to deflect in a forward direction thereby releasing the clip member from engagement with the retaining plate and allowing removal of the parallel.

For a better understanding of these and other aspects of the present invention, reference should be made to the following detailed description taken in conjunction with the accompanying drawings in which like reference numerals and characters designate like parts throughout the figures thereof.

20

BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature and objects of the present invention, references in the detailed description of the preferred embodiment set forth below shall be made to the accompanying drawings in which:

- FIG. 1 is a top perspective view of standard machine vise shown in phantom outline and equipped with a clip system for holding parallels in place along the respective jaw of the vise in accordance with the present invention;
- FIG. 2 is an exploded view in perspective of the present clip system shown in association with one of the respective vise jaws viewed in FIG. 1;
- FIG. 3 is a top plan view of the present clip system assembled in place upon the vise jaw of FIG. 2;
- FIG. 4 is a front elevation view of the assembled clip system illustration in FIG 3;
- FIG. 5 is a detailed plan view of the clip member used in accordance with the present invention;
- FIG. 6 is a cross-sectional view of the assembled clip system taken along the line 6-6 of FIG. 4;
- FIG. 7 is a cross-sectional view of the assembled clip system taken along the line 7-7 of FIG. 4; and
- FIG. 8 is a forward elevation view taken along the line 8-8 of FIG. 4 illustrating the retaining plate used in accordance with the present invention.

For a better understanding of these and other aspects of the present invention, reference should be made to the following detailed description taken in conjunction with the accompanying drawings.

20

25

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings and particularly at first to FIG. 1, an improved clip system, generally designated 10, is shown in operating position assembled to the respective jaws 12 of a standard machine vise 14 to retain separate parallels 16 along the opposed surfaces of the jaws. The vise 14, shown in phantom outline, is a conventional tool commonly used to hold a workpiece (not shown) in machines such as drill presses, milling machines and the like having a stationary head 14a and a movable head 14b supported on a base 15. Each of the jaws 12 are attached firmly to the body of the vise 14 and removable from the respective heads 14a and 14b by mean of machine bolts 18 or the like secured through circular openings in the jaw, each opening being respectively aligned with threaded holes formed in the respective heads of the vise. The parallels 16 intended to be held in place by the present clip system 10 are the conventional type of flat, metal plates typically set against the respective jaws 12 on opposite heads 14a, 14b of the vise 14 to mount the workpiece in an exact location or attitude during machining.

Referring now to FIG. 2 in conjunction with FIG. 1, the clip system 10 includes a retaining plate 20 intended to mount flush between jaw 12 and either of the vise heads, the stationary head 14a being shown in FIG. 2 and throughout the remaining drawing figures. The retaining plate 20 is a substantially flat metal plate preferably made of a high grade of tool steel. As best viewed in FIG. 8, the retaining plate 20 is fabricated having essentially the same rectangular profile as the jaw 12 but further formed having a slotted tab 22a, described in greater detail below, extending

transversely from either side of the plate. Each retaining plate 20 is further fabricated having circular openings through the thickness of the plate intended to align with those formed in jaw 12 and vise head 14a so that machine bolts 18 may threadingly engage the vise head and secure the retaining plate firmly between the vise head and the jaw. It is noted and should be understood that the retaining plate 20 is mounted in the aforedescribed manner having the slotted tab 20a facing toward the vise head 14a and away from the jaw in order to serve the operation of the clip system 10 in accordance with the present invention.

Referring now to FIGS. 3-7 in conjunction with FIGS. 1 and 2, the clip system 10 further includes a pair of clip members 22 specially configured to engage the slotted tab 20a on either side of the retaining plate 20, thereby clamping the parallel 16 against the face of jaw 12 when assembled to the jaw with the retaining plate mounted between the jaw and vise head 14a. In this assembled state, best viewed in FIGS. 3 and 6, the clip member 22, having a substantially L-shaped cross section, is disposed alongside the assembled jaw 12, retaining plate 20 and vise head 14a to clamp respective edges of parallel 16 in place on either side of the jaw when engaged, as described below, with the slotted tab 20a of the retaining plate.

Referring particularly now to FIG. 5, clip member 22 is substantially rigid in its form yet bendable along its length between a forward cap section 22a and a rearward leg section 22d. The clip member 22 is preferably fabricated, typically by molding, of a plastic material, such as nylon, to provide strength to the clip member for clamping as well as flexibility for its spring-like engagement of the retaining plate 20. As best seen in the profile of FIG. 5, each clip member 22 is integrally formed having cap section 22a

1

5

and leg section 22d projecting in opposite directions substantially perpendicular to the main body of the clip member at the forward and rearward end thereof, respectively. Cap section 22a is a relatively thin padlike appendage at the forward end of the clip member 22 intended to fit flush to the front edge of parallel 16 and clamp it against jaw 12. Leg section 22d is a relatively thicker appendage projecting from the rearward end of the clip member 22 opposite from the cap section 22a. Intermediate of the cap section 22a and leg section 22d, a hook section 22b is formed on the clip member 22 projecting from the main body in the same direction as the cap section 22a. The hook section 22b is formed along the main body of clip member 22 a distance rearward and spaced apart from the cap section 22a that is substantially equal to the aggregate thickness of the assembled parallel 16, jaw 12 and retaining plate 20. This spacing of the hook section 22b apart from the cap section 22a allows these sections to cooperate in clamping the parallel 16 to the forward face of jaw 12 when the hook section is engaged in the slotted tab 20a. A flattened section 22c raised in the main body of clip member 22 between the hook section 22b and leg section 22d provides a reference surface for contact of the clip member with the side of vise head 14a and sets the position of the hook section 22c for proper engagement with the slotted tab 20a of the retaining plate 20.

To implement and operate the present clip system 10, therefore, the retaining plate 20 is initially secured and mounted in place between the jaw 12 and vise heads 14a, 14b on opposite sides of vise 14. When the selected parallels 16 are ready to be secured to the forward surface of the respective jaws 12, clip member 22 is placed alongside of the respective vise head 14a, 14b assembled together with the jaw and retaining plate 20 with the cap

25

10 The same than the same that the same than th 15 ļ. ļ. Ţ,

1

5

section 22a of the clip member being directed to the forward surface of the jaw to cover the edge of the parallel thereon. With the parallel 16 in place against jaw 12 and its edge inserted beneath the inwardly disposed cap section 22a, the clip member 22 is urged into engagement with retaining plate 20 alongside the respective vise head 14a, 14b with the hook section 22b fitting into and engaging the slotted tab 20a in a forwardly direction and the flattened section 22c flush against the vise head. The cap section 22a is thereby urged rearward against the edge of parallel 16 clamping the parallel flush against the jaw 12 and holding it firmly in place until the clip member 22 is released. To release the clip member 22 and remove the associated parallel 16 from jaw 12, the leg section 22d is deflected in a forward direction thereby withdrawing the hook section 22b from the slotted tab 20a and releasing the cap section 22a from the parallel.

Therefore, it is apparent that the disclosed invention provides an improved clip system for holding parallels properly in place against the jaws of a vise, particularly more suitable and effective than those parallel holding devices heretofore developed. The disclosed invention provides an improved parallel holding system that is safer and easier to use on existing machine vises and that clamps the parallel in place against the jaw of the vise without interfering with the positioning of workpiece held within. In addition, the present clip system provides a parallel holder that is easily adapted to standard machine vises and that is effective in holding parallels of various sizes in proper position against the vise jaws. Furthermore, the present invention is easy to manipulate and relatively inexpensive to manufacture and implement on existing vises.

5

Hart Hart Ţ

20

25

Obviously, other embodiments and modifications of the present invention will readily come to those of ordinary skill in the art having the benefit of the teachings presented in the foregoing description and drawings. For example, the slotted tab 20a described and shown on one surface of the retaining plate 20 may be alternatively provided on both front and back surfaces of the plate or as a further modification, the tab may be slotted through its thickness to provide engagement with the hook section 22b of clip 22 in accordance with the present invention. It is therefore to be understood that various changes in the details, materials, steps and arrangement of parts, which have been described and illustrated to explain the nature of the invention, may be made by those skilled in the art within the principle and scope of the invention as expressed in the appended Claims.

5

6

7

1

2

3

4

5

6

CLAIM

What is claimed:

	1.	A s	system	for	holding	a	parallel	in	place	agains	st the	jaw	of	a
vise, co	ompri	sing	:											
1							01-	. :	1	11-	- C 41	•		. 1

- a plate member adapted to mount flush against the back of the jaw and formed having a pair of slotted tabs extending from either side thereof; and
- a pair of clip members each integrally formed along the length thereof having an intermediate hook section adapted to engage a respective one of the slotted tabs and a forward cap section to clamp flush against the parallel upon the front of the jaw when the hook section is engaged with the respective tab.
- 2. A parallel holding system according to Claim 1, wherein each of said clip members further comprise a rearward leg section adapted to deflect the hook section from the slotted tab thereby releasing the engagement thereof.
- 3. A system for holding a parallel in place against the jaw of a vise head, comprising:
- a plate member adapted to mount flush between the jaw and the vise head and formed having extended tabs on either side; and
- a pair of clip members each formed along the length thereof to engage the tabs forwardly along either side of said plate member and to clamp the parallel rearward against the jaw.

2

1

2


3


4


- 4. A parallel holding system according to Claim 3, wherein the extended tabs on either side of said plate member are slotted.
- 5. A parallel holding system according to Claim 4, wherein each of said clip members further comprise:
- a hook section formed intermediate of the length of said clip member to engage a respective one of the slotted tabs of said plate member; and
- a cap section formed at the forward end of the length of said clip member to clamp the parallel flush against the jaw when said hook section is engaged with the respective slotted tab.
- 6. A parallel holding system according to Claim 5, wherein each of said clip members further comprise:
- a leg section formed at the rearward end of the length of said clip member to deflect said hook section from engagement with the respective slotted tab thereby releasing said clip member from said plate member for removal of the parallel from the jaw.


ABSTRACT OF THE DISCLOSURE

An improved clip system is disclosed for holding parallels in place against the respective jaws of a vise. The clip system comprises a pair of specially configured clip members adapted to releasably engage a retaining plate mounted flush between the jaw and the vise, the retaining plate being formed having a slotted tab extended from either side of the plate for engaging a respective one of the clip members. Each clip member is integrally formed having a hook section inwardly disposed at an intermediate position along its length to engage the slotted tab in a forwardly direction and a cap section inwardly disposed at the forward end of the clip member to clamp flush against the parallel and hold it firmly against the jaw when the hook section is engaged with the slotted tab. The clip members are further formed each having an outwardly disposed leg section intended to deflect in a forward direction thereby releasing the clip member from engagement with the retaining plate and allowing removal of the parallel.









Attorney's	
Docket Ño.	P603

DECLARATION AND POWER OF ATTORNEY - ORIGINAL APPLICATION

As a below-named inventor, I hereby declare that:

Federal Regulations \$1.56(a).

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled CLIP SYSTEM
FOR HOLDING VISE PARALLELS
the specification of which (check one)

\[
\begin{array}{c} \times \text{ is attached hereto} \\
\text{ was filed on } \text{ as } \text{ as } \\
\text{ Application Serial No. } \\
\text{ and was amended on } \text{ (if applicable).} \end{array}
\]
I hereby state that I have reviewed and understand the content of the above-identified specification, including claims, as amended by any amendment referred to above.

amendment referred to above.

If

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of

I hereby claim foreign priority benefits under Title 35, United States Code, \$119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign App	lication(s)		Prior Claim	
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, \$120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, \$112, I

acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, \$1.56(a), which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

				
(Ap)	plication Serial No.)	(Filing D	ate)	(Status-patented,
				pending, abandoned)
(Apr	olication Serial No.)	(Filing D	2+01	(Status-patented,
(1121	prioación berrar no.,	(FIIII)	ace,	pending, abandoned)
				pending, abandoned)
I he	ereby appoint the follow	wing attorney	and/or a	gent(s) to prosecute
this	s application and to tra	ansact all bu	siness in	the Patent and
Trac	demark Office connected	therewith:		
	Armond M. Manne Tre	December 2	D 17	00.010
	Armand M. Vozzo, Jr.,	Esquire	Reg. No.	28,918
SENI	O CORRESPONDENCE TO:		DIRECT T	ELEPHONE CALLS TO:
	Armand M. Vozzo, Jr.,	Esquire		
16 (3) 200	350 South Main Street		(215) 34	8-4733
# F	Suite 117			
	Doylestown, PA 18901			
IØ :≋T b/	aroby doclars that all s		a. h	- F
				of my own knowledge are and belief are believed
= to }	oe true; and further tha	t these state	omente Me	and belief are believed
kno	wledge that willful fals	se statements	and the	like so made are
	ichahla her fina an immed			C 1001 C m'-1
[18 c	of the United States Coo	de and that si	uch willfi	ul false statements may
🃜 jeor	pardize the validity of	the applicat:	ion or an	er Section 1001 of Title ul false statements may y patent issued thereon.
iad F# i			•	•
Ful!	name of sole or first	inventorJa		neehy, Jr.
	siitoi s signature 🔾 -	1	D:	ate <u>11-1-99</u>
Resi	idence 1376 Abbey Way,		19020 C	itizenship <u>U.S.A.</u>
Post	Office Address 1376	Abbey Way alem, PA 1902	0.0	
Fu l	l name of second joint i			
	ond Inventor's signature			Date
	idence		<u></u>	itizenship
	t Office Address			
Ful.	l name of third joint in	nventor, if a	ny	
Thi	rd Inventor's signature		· · · · · · · · · · · · · · · · · · ·	Date
	idence		C:	rtrzensnip
Post	t Office Address			